


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International patent classification<sup>6</sup>:</b>  <b>H02H 3/33</b>	<b>A1</b>	<b>(11) International publication number:</b> <b>WO 99/54977</b>  <b>(43) International publication date:</b> 28 October 1999 (28.10.99)
<b>(21) International application number:</b> PCT/DE99/01074  <b>(22) International filing date:</b> 9 April 1999 (09.04.99)  <b>(30) Data relating to the priority:</b> 198 18 054.3 22 April 1998 (22.04.98) <b>DE</b>  <b>(71) Applicant (for all designated States except US):</b> SIEMENS AKTIENGESELLSCHAFT [DE/DE]; • Wittelsbacherplatz 2, D-80333 Munich (DE)  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (US only):</b> BAUER, Bernhard [DE/DE]; Friedenstrasse 17, D-93053 Regensburg (DE). SCHMID, Reinhard (DE/DE); Neuprüll 20, D-93051 Regensburg (DE).  <b>(74) Joint Representative:</b> SIEMENS AKTIENGESELLSCHAFT; Postfach 22 16 34, D-80506 Munich (DE).	<b>(81) Designated states:</b> US, European Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> With the International Search Report. Before expiry of the period provided for amending the claims, will be republished if such amendments are received.	

As printed

(54) Title: POWER CIRCUIT-BREAKER(54) Bezeichnung: SCHUTZSCHALTGERÄT

## (57) Abstract

The invention relates to a power circuit-breaker, especially a differential current circuit-breaker, comprising a summation current transformer (6) which monitors a supply network (Ln). Said summation current transformer controls a tripping device (4) which is coupled to a breaker mechanism (16) for actuating a power switch (18). The aim of the invention is to provide a power circuit-breaker which can be remotely tripped in an easy and reliable manner. To this end, a trip circuit (5) is provided with a transformer (20) which is connected on the primary side thereof to the tripping device (4) via a control circuit (3). In addition, the transformer can be controlled on the secondary side thereof in order to effect a remote tripping, preferably by short circuiting.